



PRESENTATION



Timtech Corporation Ltd

Jason tai

TEL:+886-2-22219667

FAX:+886-2-22213227

mail: Jasontai@timtech.com.tw

Your Reliable One-Stop of Supplier!

1. Company Overview

2. Product Presentation


3. Product map

4 . Cooperation Customer

- **COMPANY: TIMTECH Corporation Ltd.**
- **FOUNDED: Feb.2003**
- **ADDRESS:3FL. NO.136, LIH-DER STREET.,**
- **CHUNG HO CITY, TAIPEI**
- **HSIEN, TAIWAN. R.O.C**
- **PRODUCTS: UNIVERSAL EXTERNAL
BATTERY BANK, CHARGER,ODM / OEM
BATTERY PACK**

Product Certifications

Apple " MFI " manufacture



Test Devices / Instruments



burning machine



power supplier



loader



resistance analyzer



weld machine



high-frequency machine




ultrasonic machine



milling machine




multimeter




oscillograph

Mobile power bank Application



Developing Objectives

- 1. Universal => Application unlimited**
- 2. Recycle => Environment friendly**
- 3. Long Saleable => No Stock**
- 4. Convenient for life => Let power continue working**



Product list

Small power type(< 10Wh):



MP1280



MP1900B



MP1900A



MP2500S



MP2600R

Medium power type (< 25Wh):



MP1800U2



MP5200R



MP5000S

Large power type (< 150Wh):



MP8800



MP3450D



MP3450I



MP3450L



MP3450E

Future Product Road Map

Develop 300Wh ~3000Wh Power storage system :


- a. Module function
- b. Extended function
- c. For Solar panel charged
- d. For family emergency power or outdoor application

Announce begin of 2013 ~ end of 2013




1. Applied for iPhone,iPad,Mobile phones,GPS,PSP,MP3/MP4 ...
2. Super slim: only 9 mm,
Size 9*94*42mm like iPod nano
3. High capacity 1900mAh.
4. USB output port :5.2V / 1A . It can charging iPhone 70% fully or iPad 15% within one hour
5. Micro USB charging input port : 5V / 450mA
6. Capacity display by contact the Capacity Display touched key
7. The Power ON: It can auto turn on while USB output port connected with loading device by charging cable
8. Power Off : It can auto turn off power while 20 ~30 sec after the output loading current below 2mA . It will save power when it idle . Or when the mobile phone charged be finished .
9. Capacity indicated LED:1pcs: Orange/Blue LED.


MP1900A Presentation



1. Applied for iPhone,iPad,Mobile phones,GPS,PSP,MP3/MP4 ...
2. Super Slim : Size 9*101*42mm similar to iPod nano
3. High capacity 1900mAh.
4. Built-in Apple 30 pin connector & USB output port :5.2V / 1A . It can charging iPhone 70% fully or iPad 15% within one hour
5. Micro USB 5V charging input port
6. Capacity display by contact the Capacity Display touched key
7. The Power ON: It can auto turn on while USB output port connected with loading device by charging cable
8. Power Off : It can auto turn off power when 20~30 sec after the output loading current below 2mA . It will save power when it idle . Or when the mobile phone charged be finished .
9. Capacity indicated LED:1pcs: Orange/Blue LED.



Built –in Apple 30 pin connector can charge the Apple devices directly and no need to connect to other redundant cable.



USB port can charge for Sumsung Galaxy or other mobile devices.
Check battery capacity by Contact the Capacity Display touched key

Made for

iPod iPhone iPad




it can directly charging iPhone 70% fully or iPad 25% within one hour without charged cable

1. Applied for iPhone, iPad, Mobile phones, GPS, PSP, MP3/MP4
2. MP2500S size: 22.5 * 32 * 79 mm
3. MP5000S size : 22.5 * 32 * 121mm
4. High capacity 2500 / 5000mAh.
5. High-current output 2.1A.
6. Micro USB smart charged port
7. 3 output ports : Apple 30pin connector / Micro USB connector / USB port ; charge for different mobile phone or Tablet PC.
8. Capacity display by contact the Capacity Display touched key
9. The Power ON: Auto turn on. it can auto turn on while the output port connected with loading device by charging cable or plug in it .
10. Power Off : Auto turn off. It can auto turn off power when 30 sec after the output loading current below 2mA . It will save power when it idle.
11. Capacity indicated LED: 1pcs: Orange/Blue LED.

MP2500S & MP5000S

Made for


iPod iPhone iPad



Smart charging advantage :

1. Avoid be damaged the output port of Charger .
2. Shorten charging time .

MP2500S & MP5000S





1. Applied for iPhone,iPad,Mobile phones,GPS,PSP,MP3/MP4 and so on.
2. Small in size:22 mm (diameter) * 94mm (length)
3. High capacity 2600mAh, Can charge iPhone for 1.2 times.
4. 1A High-current output. It can charging iPhone 70% fully or iPad 15% within one hour
5. The Power ON/ Capacity Display push button:
Push : Power ON/Capacity Display
Power Off : Auto turn off
6. Capacity indicated LED:1pcs:
Orange/Blue LED
7. Input voltage/current of Micro USB port : 5V/0.45A
8. Output voltage/current of USB port : 5.2V/1A
9. Charging time: 5~6 hours.



Smart charging advantage :

- 1. Avoid be damaged the output port of Charger .**
- 2. Shorten charging time .**

- 1. Application: For iPhone / iPad / ipod, Tablet PC mobile phones, PDA,PSP and so on..**
- 2. Small in size:22 mm (diameter) * 172.5mm (length)**
- 3. High capacity 5200mAh.**
- 4. The Power ON/ capacity display push button:**
Push : Power ON/capacity display
Power Off : Auto turn off
- 5. Capacity indicated LED:1pcs:**
Orange/Blue LED
- 6. Smart input voltage/current of Micro USB port : 5V / 0.3 ~ 0.9A**
- 7. Output voltage/current of USB port : 5V/2.1A ; it can charging iPhone 70% fully or iPad 25% fully within one hour**
- 8. Charging time: 5~9 hours.**



Battery Case “ made for iPhone 4/4S”

MP1280



1. Unique charging circuit design: only supply power for iPhone 4/4S, not charge to the internal battery of iPhone 4/4S, in order to extend the iPhone's internal battery cycle life (charge frequency will easily damage internal battery cycle life) and working time.
2. Freely replacing the battery pack as user demand.
3. Charging battery case & iPhone 4/4S at same time. It also can translate data between Laptops with iPhone 4/4S by attached USB to Micro USB cable.
4. Ultra-thin: 15mm thickness.
5. Apple certification 'Made for iPhone', CE, ROHS.



1. High capacity (5800mAh) for charging your devices
2. Two USB port (A & B port): it can charge two mobile phone at same time. A port special for Apple device fast charging . B port special for Samsung Galaxy and Apple device slow charging
3. Output current total 2.1A (A+B port).
4. The Power ON: Auto turn on. it can auto turn on while the output port connected with loading device by charging cable .
5. Power Off : Auto turn off. It can auto turn off power when 30 sec after the output loading current below 2mA . It will save power when it idle.
5. Micro USB Smart input charging current from 0.5A to 0.9A .It will depend on AC power adapter's output current capability to auto modify .
6. with flashlight LED & alarm Buzzer
7. with charging/discharging indicator
8. With universal connector cable

Smart charging advantage :

1. Avoid be damaged the output port of Charger .
2. Shorten charging time .

Universal External Battery Bank. MP8800 (30Wh Tablet PC type)



1. This product is design for Tablet PC & Laptops
2. Light weight (0.3kg), Small dimension, fashion appearance
3. **Two independent Output ports :**
 - a. **DC OUT port :** 4 scales output voltage /current: 8.4V,12V,16V,19V (adjustable) / 4A
 - b. **USB port :** output voltage/current (5.25V / 1.2A)
4. With pass through charging function
5. With uninterrupted power system function
6. Wide input charging voltage range: 8~20V
7. Charging time: 3~4 hours
8. Three charging method:
 - a. Power adapter
 - b. Car charger
 - c. Solar panel charger



1. Light weight (0.45kg), Small dimension ,fashion appearance
2. **Two output port :**
 - a. **DC OUT port :**
8 scales output voltage/current
(5V,6V,7.5V,9V,12V,14V,16V,19V/4~4.5A)
 - b. **USB port's output voltage/current :**
5.25V / 2.0A
3. The voltage scale automatic locked function
4. With battery capacity extended function
5. With pass through charging function
6. With uninterrupted power system function (UPS)
7. Wide input charging voltage range:
8~20V
8. Shorter charging time: 3~4 hours
9. Three charging method : by
 - a. AC Power adapter
 - b. Car charger
 - c. Solar panel charger

Universal External Battery Bank.

MP3450L (58Wh Laptops type)



1. Adopt MCU intelligent control design. Auto scan Laptop's demand voltage to adjust output voltage for laptops automatically
2. Light weight(0.45kg), Small dimension, fashion appearance.
3. **Two independent output port :**
 - a. **DC OUT port :**
 - (1) Auto mode:10V~19V for Laptops
 - (2) Manual mode:
10V/12V/14V/16/18V/19V by manual
Output current:4~4.5A
 - b. **USB port :**
voltage/current(5.25V/1.5A)
4. The voltage scale automatic locked function.
5. With uninterrupted power system function.
6. With battery capacity extended function
7. With pass through charging function
8. Three charging method : by
 - a. AC Power adapter
 - b. Car charger
 - c. Solar panel charger

Universal External Battery Bank. MP3450E (58Wh Economy type)



1. This product is economic and practical
2. Light weight (0.4kg), Small dimension, fashion appearance
3. **Two independent Output ports :**
 - a. **DC OUT port :** 4 scales output voltage /current: 8.4V,12V,16V,19V (adjustable)/ 3.5 ~ 4A
 - b. **USB port :** output voltage/current (5.25V / 1.2A)
4. With battery capacity extended function
5. With pass through charging function
6. With uninterrupted power system function
7. Wide input charging voltage range: 8~20V
8. Charging time: 3~4 hours
9. Three charging method:
 - a. Power adapter
 - b. Car charger
 - c. Solar panel charger

Universal External Battery Bank.

MP3450I (58Wh Industry / Industry Type)

Description:

The fixed output voltage is specially for instrument or industry outdoor

Features:

- ◆ The output voltage is adjusted by the dip switch of V setting port
- ◆ 16 scales output voltage : 5V , 5.5V , 6V , 6.5V , 7.5V , 8.4V , 9V , 9.5V , 11V , 12V , 13V , 14V , 15V , 16V , 18V , 19.5V
- ◆ The output current : 4A
- ◆ battery capacity :60W;
- ◆ The high working temperature for industry : -20~85 °C
- ◆ Low capacity alarm : battery capacity < 3 ~5%
- ◆ wide Charging voltage :12 ~24 V
- ◆ The function uninterrupted Power system
- ◆ Control the battery's ON/Off by external devices
- ◆ UL (AC Power adapter) / CE certificate



MP3450 Industry / Industry Type

Battery Cell	Li-ion /(2600mAH) 6s1p	60W battery power
Output Current	4A (continual)	4.5A (max)
DC in charging Voltage	12 ~24 V	It can pass through charge with AC power adaptor
Fast Charging Current / time to battery cell	800-1000mA / 3.5-5H	When output Load Current<2±0.5A
Charging indication	1 pc. Green/Red LED	Red : on charging Green : 85-95% fully
Power on/off indication	1pc Red LED	
Capacity indication	7pcs Green LED	
Low capacity alarm	Battery capacity < 3 ~5 %	
Output Over Current protection	5~7A	
AC power adaptor input/output Voltage	AC 100V~240V	Optional .
	DC 16V~24V/3.5A	
Typical Weight	430g	
Storage Temperature	1 month : -20~60℃	rate is more the 90%

Universal External Battery Bank.

MP3460 (Extended capacity type)



1. Battery Capacity: 58Wh
2. Capacity indication: 8pcs green LED
3. Work with MP3450D / MP3450L / MP3450E / MP3450I for extended capacity to 116Wh
4. Typical weight : 374g

Cooperation partners 😊

forward

TUNEWEAR
WEAR THE MUSIC, HEAR THE TONES

ICCNEXERGY
Intelligent Power Solutions

Mr. Battery
電池先生

greencell

Tekkeon

ZUKO
POWER TO GO!

nu
Simply Better

MARWARE
The Leading Wave of the Mobile Community.

OPTIUPS
Protect and Serve




imagination at work

msi innovation with style

JABIL

decell | accessories



~Thanks for Your Time~



Your Reliable One-Stop of Supplier!